


FEATURES

- DOUBLE LAYER CONSTRUCTION
- LOW ESR
- SUITABLE FOR FLOW SOLDERING
- LEAD-FREE FINISH

RoHS Compliant
includes all homogeneous materials

*See Part Number System for Details



CHARACTERISTICS

Rated Voltage Range	5.5VDC	
Rated Capacitance Range	0.047F ~ 1.0F (47,000µF ~ 1,000,000µF)	
Operating Temp. Range	-25°C ~ +70°C	
Capacitance Tolerance	+80%/-20% (Z)	
Load Life Test @ 70°C 1,000 hours	Δ Capacitance Change	Less than ±30% of initial measured value
	Maximum ESR	Less than 400% of the specified maximum value
Temperature Characteristics -25°C & +70°C	Δ Capacitance Change	Within +30% of 20°C value
	Maximum ESR	Less than 5x 20°C value
Shelf Life @ +70°C (1,000 hours)	Δ Capacitance Change	Less than ±30% of initial measured value
	Maximum ESR	Less than 400% of the specified maximum value


**Super Capacitor
Application Guide**

STANDARD VALUES AND SPECIFICATIONS

NIC P/N	Case Size (mm)	Capacitance (F)	Holding Voltage (VDC min.)*	Max. Leakage Current @ minutes (µA)	Max. ESR @ 1KHz (Ω)
NEZBN473Z5.5V13.5X7.5F	13.5X7.5	0.047	4.0	69 @ 30 minutes	25
NEZBN104Z5.5V13.5X7.5F	13.5X7.5	0.1	4.0	100 @ 30 minutes	25
NEZBN224Z5.5V13.5X7.5F	13.5X7.5	0.22	4.0	135 @ 30 minutes	25
NEZBN334Z5.5V13.5X7.5F	13.5X7.5	0.33	4.0	182 @ 30 minutes	25
NEZBN474Z5.5V21.5X8F	21.5X8	0.47	4.0	216 @ 30 minutes	20
NEZBN105Z5.5V21.5X8F	21.5X8	1.0	4.0	315 @ 30 minutes	20

*Minimum voltage at 24 hours after charging for 1 hour at 5VDC.

PART NUMBER SYSTEM



PRECAUTIONS

Please review the notes on correct use, safety and precautions found at https://www.niccomp.com/resource/files/double/Double_Layer_Capacitor_Guide_0810-RevBrA7.pdf
If in doubt or uncertainty, please review your specific application - process details with NIC's technical support personnel: tpmg@niccomp.com

CASE DIMENSIONS (mm)

NIC P/N	DIMENSIONS (mm)					
	D max.	H max.	S ± 0.3	L ± 1.0	d ₁ ± 0.1	d ₂ ± 0.1
NEZBN473Z5.5V13.5X7.5F	13.5	7.5	5.0	6.0	1.2	0.5
NEZBN104Z5.5V13.5X7.5F	13.5	7.5	5.0	6.0	1.2	0.5
NEZBN224Z5.5V13.5X7.5F	13.5	7.5	5.0	6.0	1.2	0.5
NEZBN334Z5.5V13.5X7.5F	13.5	7.5	5.0	6.0	1.2	0.5
NEZBN474Z5.5V21.5X8F	21.5	8.0	5.0	6.0	1.2	0.5
NEZBN105Z5.5V21.5X8F	21.5	8.0	5.0	6.0	1.2	0.5

