

NEW

+260°C Rated

NEW

**SAC ALLOY
Compatible**
230 - 260°C Rated



**Liquid Electrolyte Aluminum Electrolytic Capacitors
Surface Mount Vertical Can (V-Chip)**

**NASE
NAWE
NAWT
NAZK
NAZT
NAZU
Series**

SIX NEW Series of SMT V-Chip Aluminum Electrolytic Capacitor products from NIC

• Featuring +260°C soldering heat ratings [2X Reflow: 4mm 5mm 6.3mm & 8mm sizes]

NASE: +85°C general purpose; 2Khr; 0.1uF - 1000uF; 6.3V - 50VDC ; 4mm 5mm 6.3mm 8mm & 10mm


NAWE: +105°C wide temp; 1Khr; 0.1uF - 1000uF; 6.3V - 50VDC ; 4mm 5mm 6.3mm 8mm & 10mm

NAWT: +105°C wide temp; 2Khr; 0.1uF - 1000uF; 6.3V - 50VDC ; 4mm 5mm 6.3mm 8mm & 10mm

NAZK: +105°C Low ESR; 2Khr; 4.7uF - 1000uF; 6.3V - 35VDC ; 4mm 5mm 6.3mm 8mm & 10mm

NAZT: +105°C Low ESR; 2Khr & 5Khr; 4.7uF - 1000uF; 6.3V - 50VDC ; 4mm 5mm 6.3mm 8mm 10mm 12.5mm & 16mm

NAZU: +105°C Low ESR; 3Khr; 10uF - 330uF; 6.3V - 50VDC ; 5mm & 6.3mm [reduced sizes]



NIC Catalog
ELECTROLYTIC CAPACITORS

81 Product Series

- Aluminum & Tantalum E-Caps
- Solid Polymer Electrolyte
- Hybride & Liquid Electrolyte
- +85°C, +105°C, +125°C
- 1000 - 10,000 hour ratings
- SMT: V-Chip & Flat Chip
- Radial LDD
- Snap-In & Screw Terminal

**ORDER
FREE
SAMPLES
ON-LINE**

www.niccomp.com/sample

nic [®] **NIC Components Corp.**

www.niccomp.com | www.lowESR.com | www.SMTmagnetics.com