



Material Composition Declaration

© Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.

This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.

Adobe Reader version 7.0.5 is required to complete this declaration.

1752-2 1.1	IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x	Form Type * Distribute	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informat
-------------------	--	----------------------------------	---

Supplier Information

Company Name * NIC Components Corp.	Company Unique ID	Unique ID Authority	Response Date * 2021-07-06	Response Document ID				
Contact Name * Michael Mack	Title - Contact Technology Development Mana	Phone - Contact * 631-396-7500	Email - Contact * mike.mack@niccomp.com	Duplicate Contact -> Authorized Representative				
Authorized Representative * Michael Mack	Title - Representative Technology Development Mana	Phone - Representative * 631-396-7500	Email - Representative * rohs@niccomp.com	Supplier Comments or URL for Additional Information				
Requester Item Number	Mfr Item Number	Mfr Item Name	Effective Date	Version	Manufacturing Site	Weight *	UOM	Unit Type
	NTPH B Case Series suffix"F"		2004-10-01			0.0673	g	Each
Alternate Recommendation				Alternate Item Comments				

Manufacturing Process Information

Terminal Plating / Grid Array Material Other	Terminal Base Alloy Other	J-STD-020 MSL Rating 3	Peak Process Body Temperature 245 C	Max Time at Peak Temperature 10 seconds	Number of Reflow Cycles 2
Comments Terminal Plating Copper/Nickel/Palladium/gold					

Save the fields in this form to a file

Export Data

Import fields from a file into this form

Import Data

Clear all of the fields on this form

Reset Form

Lock the fields on this form to prevent changes

Lock Supplier Fields

RoHS Material Composition Declaration

Declaration Type *

Detailed

RoHS Directive 2002/95/EC | **RoHS Definition:** Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium

Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.

RoHS Declaration *

1 - Item(s) does not contain RoHS restricted substances per the definition above

Supplier Acceptance *

Accepted

Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.

Declaration Signature

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

		Item/SubItem Name		Homogeneous Material		Weight	Unit of Measure	Level		Substance Category	Substance		CAS		Exempt	Weight	Unit of Measure	Tolerance		PPM				
+I	-I			+M	-M			+C	-C		+S	-S						-	+					
		NTPH B Case Series				Tantalum Anode	28.1	mg		Supplier	Tantalum					7440-25-7				28.1	mg			
		Electrolyte		1.7		mg		+C	-C	Supplier	Polymer		+S	-S	Polymer	non-disclos				1.7	mg			
		Cathode Layer C		0.1		mg		+C	-C	Supplier	Graphite		+S	-S	Graphite	7782-42-5				0.0281	mg			
								+S	-S	Carbon black		1333-86-4			0.0281	mg								
								+S	-S	Formaldehyde resin		non-disclos			0.014	mg								
								+S	-S	Phenol resin		non-disclos			0.0281	mg								
								+S	-S	Phenol		108-95-2			0.0017	mg								
		Cathode Layer S		1.9		mg		+C	-C	Supplier	Metals		+S	-S	Sliver	7440-22-4				1.52	mg			
								+S	-S	Epoxy resin		9003-36-5			0.19	mg								
								+S	-S	Phenol resin		non-disclos			0.095	mg								
								+S	-S	others		non-disclos			0.095	mg								
		Conductive Adh		1.5		mg		+C	-C	Supplier	Metals		+S	-S	Silver	7440-22-4				1.2	mg			
								+S	-S	Epoxy resin		9003-36-5			0.15	mg								
								+S	-S	Phenol resin		non-disclos			0.075	mg								
								+S	-S	others		non-disclos			0.075	mg								
		Mold Encapsulat		22.68		mg		+C	-C	Supplier	Silicone		+S	-S	Silica	60676-86-0				18.144	mg			
								+S	-S	Epoxy resin		9003-36-5			2.268	mg								
								+S	-S	Resin Hardener		non-disclos			0.9072	mg								
								+S	-S	others		non-disclos			1.3608	mg								
		Lead Frame		10.283		mg		+C	-C	Supplier	Metals		+S	-S	Iron	7439-89-6				6.00482	mg			
								+S	-S	Nickel		7440-02-0			4.21603	mg								
								+S	-S	Maganese		7439-96-5			0.04068	mg								
								+S	-S	Silicon		7440-21-3			0.01582	mg								

+S	-S	Aluminum	7429-90-5			0.00565	mg															
+M	-M	Terminal Plating	1.017	mg	+C	-C	Supplier	Metals	+S	-S	Copper	7440-50-8					0.66896	mg				
					+S	-S	Nickel	7440-02-0			0.32883	mg										
					+S	-S	Palladium	7440-05-3			0.01469	mg										
					+S	-S	Gold	7440-57-5			0.00452	mg										
+M	-M	Marking Ink	0.02	mg	+C	-C	Supplier	Ink	+S	-S	Titanium-dioxide	13463-67-7					0.011	mg				
					+S	-S	Others	non-disclos			0.009	mg										