

NANP35X7AUS0R915G1F

ISM / LoRa PCB Antenna



Description


The NANP35X7AUS0R915G1F is a rigid PCB antenna designed for ism / LoRa applications. It operates within the frequency ranges of 902 ~ 928 MHz making it perfect for use in Wireless alarm and security systems, Industrial monitoring and control, IOT applications and Smart Meters.



Features

- Dual Band Frequency
- Customizable cable type and cable length
- Rigid PCB Type
- RoHS compliant

Part Number Breakdown



Standard Part Number Listing

| Part Number | Connector | Cable Length | Cable Type | Cable Orientation |
|---------------------------|-----------|--------------|------------|-------------------|
| NANP35X7AUS0R915G1X100AHF | IPEX MHF | 100 mm | RF1.13 | Horizontal |

The table represents assembled part numbers available on www.niccomp.com from standard connector and cable options. For options not listed above please contact NIC"

NANP35X7AUS0R915G1F


ISM / LoRa PCB Antenna



Specifications


| | |
|-----------------------------|---------------|
| Frequency Ranges | 902 ~ 928 MHz |
| Center Frequency | 915 MHz |
| Gain | 2 dBi |
| V.S.W.R | 2.0 max. |
| Efficiency | 67.5% |
| Polarization | Linear |
| Impedance | 50Ω |
| Operating Temperature Range | -40°C ~ 85°C |
| Storage Temperature | -5°C ~ 40°C |
| Relative Humidity | 10 ~ 70% |
| Mounting Method | Adhesive |
| RoHS Compliant | Yes |

Dimensions




Return Loss and Smith Chart

Return Loss



Smith Chart







NANP35X7AUS0R915G1F

ISM / LoRa PCB Antenna



Radiation Patterns

3D Gain Patterns @ 915 MHz



NANP35X7AUS0R915G1F

ISM / LoRa PCB Antenna



Efficiency Table

| Frequency(MHz) | 902 | 904 | 906 | 908 | 910 | 912 | 914 | 915 | 916 | 918 | 920 | 922 | 924 | 926 | 928 |
|-----------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Efficiency(dB) | -1.8 | -1.7 | -1.7 | -1.6 | -1.6 | -1.7 | -1.7 | -1.7 | -1.7 | -1.8 | -1.9 | -1.8 | -1.8 | -1.9 | -1.9 |
| Efficiency (%) | 66.7 | 67.2 | 67.8 | 69.1 | 69.4 | 67.7 | 67.4 | 67.5 | 67.8 | 66.4 | 65.2 | 66.6 | 65.7 | 64.2 | 64.5 |
| Peak Gain (dBi) | 1.9 | 1.9 | 2.0 | 2.1 | 2.1 | 2.0 | 2.0 | 2.0 | 2.1 | 2.0 | 2.0 | 2.1 | 2.1 | 2.0 | 2.1 |

Efficiency Vs. Frequency

